


## SFL PRO 6X (909 250)

- Surge protection with monitoring device and disconnecter
- Interference suppressor filter
- Visual operating state (green) and fault indication (red)



Figure without obligation



Basic circuit diagram SFL PRO 6X



Dimension drawing SFL PRO 6X

Surge protective multiple socket outlet with mains filter.

Type	SFL PRO 6X
Part No.	909 250
SPD according to EN 61643-11 / IEC 61643-11	type 3 / class III
Nominal a.c. voltage ( $U_N$ )	230 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) ( $U_C$ )	255 V (50 / 60 Hz)
Nominal load current (a.c.) ( $I_L$ )	16 A
Voltage drop in percent for $U_C/I_L$ ( $\Delta U$ )	$\leq 0.5$ %
Nominal discharge current (8/20 $\mu$ s) ( $I_n$ )	3 kA
Total discharge current (8/20 $\mu$ s) [L+N-PE] ( $I_{total}$ )	5 kA
Combined wave ( $U_{OC}$ )	6 kV
Combined wave [L+N-PE] ( $U_{OC total}$ )	10 kV
Voltage protection level ( $U_P$ )	$\leq 1.5$ kV
Response time [L-N] ( $t_A$ )	$\leq 25$ ns
Response time [L/N-PE] ( $t_A$ )	$\leq 100$ ns
Max. mains-side overcurrent protection	B 16 A
Short-circuit withstand capability for max. mains-side overcurrent protection ( $I_{SCCR}$ )	1.5 kA <sub>rms</sub>
Temporary overvoltage (TOV) [L-N] ( $U_T$ ) – Characteristic	335 V / 5 sec. – withstand
Temporary overvoltage (TOV) [L-N] ( $U_T$ ) – Characteristic	440 V / 120 min. – safe failure
Temporary overvoltage (TOV) [L/N-PE] ( $U_T$ ) – Characteristic	335 V / 120 min. – withstand
Temporary overvoltage (TOV) [L/N-PE] ( $U_T$ ) – Characteristic	440 V / 5 sec. – withstand
Temporary overvoltage (TOV) [L+N-PE] ( $U_T$ ) – Characteristic	1200 V + $U_{REF}$ / 200 ms – safe failure
Fault indication	red light
Operating state indication	green light
Number of ports	2
Operating temperature range ( $T_U$ )	-20 °C ... +40 °C
Connecting cable	approx. 2000 mm
Number of socket outlets	6
For mounting on	earthed socket outlets DIN 49440 / DIN 49441
Enclosure material	thermoplastic, black / silver, UL 94 V-1
Place of installation	indoor installation
Degree of protection	IP 20
Dimensions	571 x 72 x 43 mm
Mains filter	acc. to EN 60393-1 (DIN VDE 0565-3)
Attenuation for f = 1 MHz, balanced	$\geq 32$ dB
Attenuation for f = 1 MHz, unbalanced	$\geq 30$ dB
Weight	1,1 kg
Customs tariff number	85369010
GTIN	4013364132566
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.