

Features:

- * 4 stage charging
- * Charger for lead-acid batteries
- * Energy saving mode
- * Front panel indicator for operation status
- * Thermostatically controlled cooling fan
- * Protections: Over voltage / Over temp. / Output short
- Input polarity reverse
- * Approvals: EMC/LVD/e13/CE/SGS/ROHS/ISO 9001



Made in Taiwan

SPECIFICATION

Automatic Battery Charger	AD-5012
INPUT RANGE (volt)	230 AC +/- 10%
INPUT FREQUENCY	50~60 Hz
INPUT SOCKET	IEC plug
OUTPUT VOLTAGE(volt)	12 DC
Max. OUTPUT POWER	720W – 50A
MULTI-RATE CHARGING FUNCTION	Select by Slide Switch
4 STAGE CHARGING	Soft Start> Bulk> Absorp> Maint
RECOMMENDED BATTERY CAPACITY	75Ah~500Ah
OVER VOLT PROTECTION	Lower Output Current
SHORT CIRCUIT PROTECTION	Yes (by fuse)
OVER HEAT PROTECTION	Lower Output Current
REVERSE POLARITY PROTECTION	Yes (by fuse)
OPERATING TEMPERATURE RANGE(C)	-10 ~ +50
DIMENSION (L*W*H)	325*198*83mm
NET WEIGHT	3.3 Kg