


BSP M2 BE 48 (926 225)


- High degree of protection for two single lines
- For installation in conformity with the lightning protection zone concept at the boundaries from $0_B - 2$ and higher



Figure without obligation



Basic circuit diagram BSP M2 BE 48



Dimension drawing BSP M2 BE 48

Space-saving surge arrester module for protecting two single lines sharing a common reference potential and unbalanced interfaces.

Type	BSP M2 BE 48
Part No.	926 225
SPD class	<input type="checkbox"/> TYPE 2 <input checked="" type="checkbox"/> TYPE 2+P
Nominal voltage (U_N)	48 V
Max. continuous operating voltage (d.c.) (U_C)	54 V
Max. continuous operating voltage (a.c.) (U_C)	38.1 V
Nominal current at 45 °C (I_N)	0.75 A
D1 Lightning impulse current (10/350 μ s) per line (I_{imp})	1 kA
C2 Total nominal discharge current (8/20 μ s) (I_n)	20 kA
C2 Nominal discharge current (8/20 μ s) per line (I_n)	10 kA
Voltage protection level line-line for I_n C2 (U_p)	≤ 170 V
Voltage protection level line-PG for I_n C2 (U_p)	≤ 115 V
Voltage protection level line-line at 1 kV/ μ s C3 (U_p)	≤ 140 V
Voltage protection level line-PG at 1 kV/ μ s C3 (U_p)	≤ 70 V
Series impedance per line	1.8 ohm(s)
Cut-off frequency line-PG (f_c)	8.7 MHz
Capacitance line-line (C)	≤ 0.35 nF
Capacitance line-PG (C)	≤ 0.7 nF
Operating temperature range (T_U)	-40 °C ... +80 °C
Degree of protection (with plugged-in protection module)	IP 20
Pluggable into	BXT BAS / BSP BAS 4 base part
Earthing via	BXT BAS / BSP BAS 4 base part
Enclosure material	polyamide PA 6.6
Colour	yellow
Test standards	IEC 61643-21, UL 497B
Approvals	UL, CSA, SIL, EAC
SIL classification	up to SIL3 ^{*)}
Weight	21 g
Customs tariff number	85363010
GTIN	4013364127043
PU	1 pc(s)

^{*)} For more detailed information, please visit www.dehn-international.com.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.