

18.600 G

OEM Pressure Transmitter Pneumatics

Applications

- ▶ compressed air network
- ▶ general mechanical engineering

Characteristics

- ▶ silicon sensor without media isolation
- ▶ accuracy 0.5 % FSO according to IEC 60770
- ▶ nominal pressure ranges from 0 ... 100 mbar up to 0 ... 6 bar



Technical Data



Input pressure range											
Nominal pressure gauge	[bar]	-1 ... 0	0,1	0,25	0,4	0,6	1	1,6	2,5	4	6
Overpressure	[bar]	3	0,5	1	1	3	3	6	10	10	20
Burst pressure	[bar]	5	1,5	3	3	3	7,5	7,5	15	25	25

Output signal / Supply	
Standard	2-wire: 4 ... 20 mA / $V_S = 8 \dots 32 V_{DC}$
Option	3-wire: 0 ... 10 V / $V_S = 14 \dots 30 V_{DC}$
	3-wire ratiometric: 10 ... 90% of V_S / $V_S = 2.7 \dots 5 V_{DC}$

Performance	
Accuracy ¹	$\leq \pm 0.5 \% \text{ FSO}$
Permissible load	2-wire: $R_{max} = [(V_S - V_{Smin}) / 0.02 A] \Omega$ 3-wire: $R_{min} = 10 k\Omega$
Influence effects	supply: 0.05 % FSO / 10 V load: 0.05 % FSO / k Ω
Response time	2-wire: $\leq 10 \text{ msec}$ 3-wire: $\leq 3 \text{ msec}$
Long term stability	$\leq \pm 0.2 \% \text{ FSO} / \text{year}$ at reference conditions
Measuring rate	1 kHz

¹ accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)

Thermal effects (Offset and Span)			
Nominal pressure P_N	[bar]	-1 ... 0	≤ 0.4
Tolerance band	[% FSO]	$\leq \pm 1$	$\leq \pm 1$
in compensated range	[°C]	0 ... 70	-20 ... 85

Permissible temperatures			
Permissible temperatures	medium: -25 ... 125 °C	electronics / environment: -25 ... 85 °C	storage: -40 ... 85 °C

Electrical protection	
Short-circuit protection	permanent
Reverse polarity protection	no damage, but also no function
Electromagnetic compatibility	emission and immunity according to EN 61326

Mechanical stability	
Vibration	10 g, 25 Hz ... 2 kHz according to DIN EN 60068-2-6
Shock	100 g / 11 msec according to DIN EN 60068-2-27

Materials			
Pressure port / housing	stainless steel 1.4301 (304)		
Seals	FKM		
Sensor	stainless steel 1.4404 (316L), silicon, glass, epoxy or RTV		
Media wetted parts	pressure port, seals, sensor		
Miscellaneous			
Permissible media	pressurized air, non-aggressive gases		
Current consumption	2-wire: max. 25 mA 3-wire voltage: max. 7 mA (short circuit current: max. 20 mA)		
CE-conformity	EMC Directive: 2004/108/EC		
Wiring diagrams			
2-wire-system (current) 		3-wire-system (voltage) 	
Pin configuration			
Electrical connections	ISO 4400	M12x1 (4-pin)	cable colours (DIN 47100)
Supply +	1	1	wh (white)
Supply -	2	2	bn (brown)
Signal + (for 3-wire)	3	3	gn (green)
Shield	ground pin	4	ye/gn (yellow / green)
Electrical connections (dimensions in mm)			
² standard: 2 m PVC cable without ventilation tube (permissible temperatur: -5 ... 70 °C) ³ different cable types and lengths available, permissible temperatur depends on kind of cable			
Mechanical connection (dimensions in mm)			
standard		option ⁴	
G1/4" DIN 3852		G1/4" EN 837	
G1/4" NPT		G1/2" EN 837	
⁴ other mechanical connections on request			

© 2016 BD|SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

Ordering code 18.600 G

18.600 G - - - - - - - -

Input	[bar]																				
	0.10	1	0	0	0																
	0.25	2	5	0	0																
	0.40	4	0	0	0																
	0.60	6	0	0	0																
	1.0	1	0	0	1																
	1.6	1	6	0	1																
	2.5	2	5	0	1																
	4.0	4	0	0	1																
	6.0	6	0	0	1																
	-1 ... 0	X	1	0	2																
	customer	9	9	9	9															consult	
Pressure	gauge					R															
Output	4 ... 20 mA / 2-wire					1															
	0 ... 10 V / 3-wire					3															
	10 ... 90% of V_S / 3-wire ratiometric					R															
	customer					9															consult
Accuracy	0.5 % FSO					5															
	customer					9															consult
Electrical connection	Male and female plug ISO 4400					1	0	0													
	Male plug M12x1 (4-pin), plastic					M	0	0													
	Cable outlet with PVC-cable ¹					T	A	0													
	customer					9	9	9													consult
Mechanical connection	G1/4" DIN 3852					3	0	0													
	G1/4" EN 837					4	0	0													
	1/4" NPT					N	4	0													
	customer					9	9	9													consult
Seals	FKM																				1
	customer																				9
Special version	standard																				0 0 0
	customer																				9 9 9
																					consult

¹ standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)

This price list contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

01.01.2014

