

Features:

- * 12V or 24V DC input
- * Modified sine wave output
- * U.P.S function
- * Automatic Battery Charger
- * Energy saving mode
- * Output voltage regulation:5%
- * High efficiency up to 91%
- * Power ON-OFF switch
- * Standby saving mode
- * Front panel indicator for operation status
- * Thermostatically controlled cooling fan
- * Topology: Microprocessor
- * Protections: Bat. Low alarm / Bat. Low shutdown / Over voltage
Over temp. / Output short / Input polarity reverse / Overload
- * Approvals: EMC/LVD/e13/CE/SGS/ROHS/ISO 9001



Made in Taiwan

SPECIFICATION

ITEM	SP-2500C	
OUTPUT POWER	CONTINUOUS POWER 2500W	SURGE POWER 5000W
STANDBY CURRENT	DC 12V <0.7A	DC 24V <0.5A
INPUT VOLTAGE	DC 12V: 10V~15V	DC 24V: 20V~30V
OUTPUT VOLTAGE	AC 220V	AC 220V
OUTPUT WAVEFORM	MODIFIED SINE WAVE	MODIFIED SINE WAVE
EFFICIENCY	>91 %	>91 %
*INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. ex. 12/24	
*OUTPUT REGULATION	+/- 5% INTELLIGENT AVR	+/- 5% INTELLIGENT AVR
*OUTPUT FREQUENCY	50Hz , 55Hz , 60Hz CRYSTAL CONTROLLED	50Hz , 55Hz , 60Hz CRYSTAL CONTROLLED
*COOLING	AUTO-OPERATION FAN	AUTO-OPERATION FAN
*OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION	OUTPUT SHORT CIRCUIT PROTECTION
*LOW BATTERY	<10.5V or 21.5V +/- 0.5V PRE ALARM	<9.5V or 20V +/- 0.5V SHUT DOWN&ALARM
*OVER HEATING	>60C PRE ALARM	>65C SHUT DOWN & ALARM
*OVER LOAD	>2500W PRE-ALARM	>2700W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE	BY FUSE
FUSE	DC 12V: 25A * 16PCS	DC 24V: 15A * 16PCS
AC OUTLET	2AC OUTLET	2 AC OUTLET
*BATTERY CHARGER	AUTO-INDICATING FULL BATTERY	AUTO-INDICATING FULL BATTERY
*CHARGER CIRCUIT	DC 12V: MAX. 10A	DC 24V: MAX. 5A
*AUTOMATICAL SWITCH	AC LINE ----- > INVERTER	INVERTER ----- > AC LINE
*TRANSFER TIME	AC LINE ----- > INVERTER 16ms	INVERTER ----- > AC LINE 16ms
DIMENSION (L*W*H)	420*169*152mm	420*169*152mm
NET WEIGHT	7.8 Kg	7.8 Kg

*MARKS ARE OUR UNIQUE FUNCTIONS.